

Plain Weave

Technical Datasheet

Lobrene® plain weave products are strong and durable polypropylene fabrics that are ideal for use in the construction of floorcoverings, underlays, scrim, laminate substrates, reinforcement, ground covers, and composite hoses.

Versatile, cost effective and recyclable, Lobrene® fabrics can easily be incorporated into a variety of membranes and can create a good bond between other materials.

At Don & Low, our flexibility allows us to produce materials with UV resistance, flame retardancy and different colours. Lobrene® fabrics are also available in a range of roll widths and lengths to suit specific customer requirements.

TEST	UNITS		LOBRENE®
Product Code			IM038H3BB
Fabric Weight	g/m ²		81
Construction	ends/10cm	Warp	124
		Weft	38
Weave Type			Plain
Tensile Strength	N/50mm	Warp	600
		Weft	600
Elongation (%)	(%)	Warp	25
		Weft	20
Shrinkage	% at 132°C	Warp	4
		Weft	2

All products are manufactured under BS EN ISO 9001.

Don & Low reserves the right to change specifications or other product information. Don & Low accepts no responsibility or liability for information provided by third parties. No warranties, express or implied, are offered regarding the suitability of any product for your use, as site conditions and customer requirements vary. Should you require further information, please contact us. Products are sold subject to the seller's terms and conditions of sale. No warranty or immunity is offered against infringement of patents or other intellectual property rights.

©Don & Low Limited, 2025. The intellectual property in the products is owned and protected by Don & Low or its licensors.